



NOTES:

- ① LENS: MADE OF CLEAR POLYCARBONATE
 - ② REFLECTOR: MADE OF SPUN ALUMINUM; PAINTED WHITE ON THE INSIDE; MECHANICALLY HELD
 - ③ LAMP: 100 WATT METAL HALIDE
 - ④ OPTICS: A ROUND PRISMATIC BOROSILICATE THERMO-RESISTANT REFRACTOR; GIVING TYPE 3 DISTRIBUTION
 - ⑤ LOCKING SYSTEM: MADE OF CAST ALUMINUM; MECHANICALLY HELD
 - ⑥ BALLAST: 100 WATT METAL HALIDE, HIGH POWER FACTOR OF 90% OR BETTER; -30°F
 - ⑦ HOUSING: MADE OF CAST ALUMINUM; MECHANICALLY HELD
 - ⑧ ADAPTOR: MADE OF CAST ALUMINUM; WELDED TO THE ARM
 - ⑨ ARM: MADE OF CAST ALUMINUM; TUBING 60mm o.d.; WELDED TO THE CENTRAL TUBING
 - ⑩ DECORATIVE SCROLL: MADE OF CAST ALUMINUM; WELDED TO THE ARM AND CENTRAL TUBING
 - ⑪ CENTRAL TUBING: MADE OF ALUMINUM; 102mm o.d. c/w A TENON PENETRATING 305mm INSIDE THE POLE; MECHANICALLY HELD
 - ⑫ POLE: MADE OF STEEL; 102mm o.d. 5mm WALL THICKNESS; WELDED TO THE BASE
 - ⑬ DECORATIVE COVER: MADE OF CAST ALUMINUM; MECHANICALLY HELD TO THE POLE
 - ⑭ BASE: MADE OF STEEL; 188mm o.d. 4mm WALL THICKNESS; WELDED TO THE ANCHOR PLATE
 - ⑮ ACCESS DOOR: MADE OF ALUMINUM; COVERING AN OPENING OF 102mm x 229mm; GIVING ACCESS TO A GROUND LUG
 - ⑯ BASE COVER: MADE OF A TWO-PIECE CAST ALUMINUM COMPONENT; MECHANICALLY HELD
 - ⑰ RECEPTACLE: DUPLEX RECEPTACLE; 15A 120V c/w WEATHERPROOF COVER
- GASKETING: NEOPRENE AND SILICONE GASKETING IS APPLIED
- HARDWARE: ALL EXPOSED SCREWS WILL BE STAINLESS STEEL
- FINISH: AN APPLICATION OF A THERMOSETTING POLYESTER POWDER COAT PAINT; COLOUR TO BE DARK BLUE TEXTURED



WHISTLER

**RESORT MUNICIPALITY of WHISTLER
TRAIL & PEDESTRIAN LIGHT DETAILS**

DRAWN BY: BL

DATE: JULY 2008

SCALE: N.T.S.

DWG. NO.: E1